

Technical Data Sheet (TDS)

Product Identification

MPN: HCUP8UV
SKU: 02-0036
UPC: 661094573667
Country of Origin: United States



Universal Polyalkylene glycol (PAG) High Viscosity 150 UV DYE

HCPRO® Universal PAG UV DYE – The Versatile Lubricant for Ultimate Performance and Protection!

Introduction

Polyalkylene Glycol (PAG) lubricants are critical components in modern automotive air conditioning (A/C) systems, especially those utilizing R134a refrigerant. These synthetic oils are specifically formulated to provide the necessary lubrication for the compressor, ensuring smooth operation, efficient heat transfer, and protection against wear under demanding conditions. The inclusion of a UV fluorescent dye in such lubricants offers a significant advantage for maintenance and diagnostics, enabling technicians to quickly and accurately locate leaks within the sealed A/C system, thereby preventing more extensive damage and costly repairs. HCPRO® Polyalkylene glycol Universal PAG with UV DYE is a product designed to fulfill these requirements, offering a combination of lubrication performance and leak detection capability.

HCPRO® Universal PAG with UV Dye is a high-performance synthetic polyalkylene glycol lubricant specifically formulated for R-134a (and R-1234yf) automotive A/C compressors. It combines all the lubrication, thermal stability, and anti-wear benefits of Universal PAG with an integrated, SAE-approved UV-fluorescent dye that enables rapid, precise leak detection under UV inspection lights.

Key Features & Benefits

- Integrated UV Dye:** SAE-approved, non-reactive fluorescent tracer for quick leak location.
- Superior Thermal Stability:** Maintains film strength at elevated temperatures.
- Enhanced Oxidation Resistance:** Extends oil life and minimizes sludge formation.
- Exceptional Lubricity:** Reduces friction and wear for smoother compressor operation.
- Corrosion & Wear Protection:** Specialized inhibitors safeguard internal components.
- Moisture Resistance:** Hygroscopic-managed formulation reduces hydrolysis risk.
- Broad Compatibility:** Works with common A/C elastomers (nylon, EPDM, PTFE, etc.)

Recommended Applications

- Automotive & Light-Commercial A/C Systems:** R-134a and R-1234yf refrigerants.
- Leak-Detection Service:** Ideal when performing pressure/leak checks or compressor replacement.
- Not for use with mineral-oil or POE (polyol ester)-based systems.**

PHYSICAL & CHEMICAL PROPERTIES

PROPERTY	TYPICAL VALUE	TEST METHOD / STANDARD
ISO Viscosity Grade	150 (ISO VG 150)	ISO 3448
Kinematic Viscosity @ 40 °C	100 cSt (typical)	ASTM D445
Kinematic Viscosity @ 100 °C	8.6 cSt (typical)	ASTM D445
Viscosity (SUS @ 100 °F)	130 SUS	ASTM D2161
Viscosity Index	150	ASTM D2270
Specific Gravity @ 20 °C	0.93	ASTM D4052
Flash Point (COC)	455 °F / 235 °C	ASTM D92
Pour Point	-31 °F / -35 °C	ASTM D97
Boiling Point	> 500 °F / 260 °C	In-house testing
Color & Appearance	Bright, clear; red/yellow tint	Visual
Solubility	Miscible with R-134a	In-house testing
Ready-to-Use	No dilution required	—
pH (1% aqueous)	7 (neutral)	ASTM D1287
UV Dye Compatibility	Integrated, non-reactive	—
VOC Content	Low	In-house testing

Performance Standards & Compliance

- Meets or exceeds:** ASTM D445, D2270, D92, D97, D974, D2783, E203, D4052, D1401; ANSI ASHRAE 97 1989; ATM D972; Modified IP48; FZG gear test; SAE UV dye requirements.

Equipment & Material Compatibility

- Compressors:** Suitable for Sanden, Nippondenso, Delphi/Harrison, and most R 134a OEM compressors.
- Elastomers & Seals:** Compatible with fluorocarbon (Viton), EPDM, PTFE, and polyamide materials; incompatible with mineral oil-lubricated systems.

Contact Information

- Phone: 1-305-549-8895
- Address: 13473 NW 19th Ln, Miami, FL 33182, USA
- Email: info@hcproproducts.com
- Office Hours: Mon - Fri | 9:00 AM - 5:00 PM EST
- Follow us on social media: [@hcproproducts](https://www.instagram.com/hcproproducts)



Storage & Handling

- Storage:** 15 °C–30 °C (59 °F–86 °F), dry, away from direct sunlight.
- Container:** Keep sealed to prevent contamination/moisture ingress.
- Shelf Life:** Up to 5 years unopened; use promptly once opened.

Packaging & Availability

Package Type	Net Volume	Case Pack
Plastic Bottle	8 oz / 237 mL	12 per case
Steel Drum	5 L, 20 L, 200 L	—
Bulk	Customer-specified	—

All packaging is made in the USA

Safety & First Aid

- OSHA Status:** Not classified as hazardous (29 CFR 1910.1200).
- Eye Contact:** Flush with water for 15 min; seek medical attention if irritation persists.
- Skin Contact:** Wash with soap and water; wear protective gloves.
- Ingestion:** Do not induce vomiting; seek immediate medical care.
- Ventilation:** Use in well-ventilated areas; refer to SDS for full guidance.

Environmental & Disposal

- Disposal:** Per local, state, federal regulations—do not release to drains or waterways.
- Avoid Release:** Do not discharge into drains, sewers or waterways.
- Recycling:** Collect and recycle used oil through authorized programs where available.

Made in USA

For Safety Data Sheet (SDS), scan the QR code or visit:

www.hcproproducts.com



hcproproducts

HCPRO®
KEEP IT RUNNING